

cations with a remote source, and for executing monetary charges according to the usage of the software comprising:

signal processing means for performing unique signal processing based on the input route of the software data; and

error processing means for conducting error processing based on the input route;

input switchover means for selecting an input route, said input switchover means comprising:

first switchover means for outputting encrypted and non-encrypted software data to said signal processing means and;

second switchover means for receiving the output from said signal processing means and directing the output of said signal processing means to said error processing means;

software management means for decoding encrypted software data and for managing monetary charges according to the usage of the software data;

data conversion means for converting decoded data outputted from said software management means to output data offered to the user; and

output route switchover means for receiving encrypted data from said input switchover means and outputting the encrypted data to said software management means, and for receiving non-encrypted software data from said input switchover means and outputting the non-encrypted software data to said data conversion section.

2. The software reproduction apparatus of claim 1 further comprising:

drive apparatus for installing a writable medium;

writing means for writing on to said medium encrypted software data obtained from the said input route prior to its output to said software management means; and

a means for reading encrypted software data written on said medium.

3. The software reproduction apparatus of claim 1 wherein said error processing means is equipped with an error check code generation section for generating new error check codes corresponding to the said writable medium.

4. A software reproduction apparatus for reproducing encrypted or non-encrypted software data received via an input route including a writable medium, a non-writable medium and by communications with a remote source, and for executing monetary charges according to the usage of the software, the software reproduction apparatus comprising:

input switchover means for selecting an input route;

software management means for decoding encrypted software data using key data from an external source and for managing monetary charges according to the usage of the software data;

data conversion means for converting decoded data outputted from said software management means to output data offered to the user; and

output route switchover means for receiving encrypted data from said input switchover means and outputting the encrypted data to said software management means, for receiving the non-encrypted software data from said input switchover means and outputting the non-encrypted software data to said data conversion means, and for outputting the encrypted software data to a writable medium.

5. The software reproduction apparatus of claim 4 further comprising:

error management means equipped with an error check code generation section for generating new error check codes corresponding to the writable medium.

005060 62645960

6. A software reproduction apparatus for reproducing encrypted or non-encrypted software data received via an input route including a storage medium and by communications with a remote source, and for executing monetary charges according to the usage of the software comprising:

input switchover means for selecting an input route according to the type of medium or communications;

software management means for decoding encrypted software data and for managing monetary charges according to the usage of the software data;

data conversion means for converting decoded data outputted from said software management means to output data for the user;

output route switchover means for receiving encrypted data from said input switchover means and outputting the encrypted data to said software management means, and for receiving non-encrypted software data from said input switchover means and outputting the non-encrypted software data for said data conversion section;

drive apparatus for installing a writable medium;

writing means for writing, on said medium, encrypted software data obtained from the said input route prior to the output of the encrypted software data to said software management means; and

a means for reading encrypted software data written on said medium.

7. A software reproduction apparatus for reproducing encrypted or non-encrypted software data received via an input route including a storage medium and by communications with a remote source, and for executing monetary charges according to the usage of the software comprising:

signal processing means for performing unique signal processing based on the input route of the software data; and

error processing means for conducting error processing based on the input route;

input switchover means for selecting an input route, said input switchover means comprising:

first switchover means for outputting encrypted and non-encrypted software data to said signal processing means and;

second switchover means for receiving the output from said signal processing means and directing the output of said signal processing means to said error processing means;

software management means for decoding encrypted software data and for managing monetary charges according to the usage of the software data;

data conversion means for converting decoded data outputted from said software management means to output data offered to the user;

output route switchover means for receiving encrypted data from said input switchover means and outputting the encrypted data to said software management means, and for receiving non-encrypted software data from said input switchover means and outputting the non-encrypted software data to said data conversion section;

drive apparatus for installing a writable medium;

writing means for writing on said writable medium encrypted software data obtained from the said input route prior to its output to said software management means; and

a means for reading encrypted software data written on said medium.

\* \* \* \* \*

005060" 0264560

SUBA 8. An apparatus comprising:  
digital information receiving means for  
receiving digital information provided via a  
communication medium;  
drive means for reading digital information  
from, and writing digital information to, a  
removable storage medium;  
information converting means for  
converting digital information received by said  
digital information receiving means and digital  
information read by said drive means into at least  
one of the group consisting of visible and audible  
data; and  
switch means for controlling a connection  
between said digital information receiving means  
and said information converting means, between  
said digital information receiving means and said  
drive means, and between said drive means and  
said information converting means.

9. The apparatus according to claim 8,  
further comprising:

deciphering means  
for deciphering digital information  
received by said digital information receiving  
means when the digital information is ciphered,  
and for providing the deciphered digital  
information to said information converting means  
for converting, and

for deciphering digital information  
read by said drive means when the digital  
information is ciphered, and for providing the  
deciphered digital information to said information  
converting means for converting.

10. The apparatus according to claim 9,  
further comprising:

billing managing means  
for managing billing based on a  
utilization of the digital information received by  
said digital information receiving means, and  
for managing billing based on a  
utilization of the digital information read by said  
drive means.

11. The apparatus according to claim 8,  
wherein said information converting means  
comprises:

extension means

for extending digital information  
received by said digital information receiving  
means when said digital information is  
compressed, and

for extending said digital  
information read by said drive means when said  
digital information is compressed.

540 A27 12. An apparatus comprising:  
a digital information receiver receiving  
digital information provided via a communication  
medium;

a drive device reading digital information  
from, and writing information to, a removable  
storage medium;

a converter converting digital information  
received by said digital information receiver and  
digital information read by said drive device into at  
least one of the group consisting of visible and  
audible data; and

a switch controlling a connection between  
said digital information receiver and said converter,  
between said digital information receiver and said  
drive device, and between said drive device and said  
converter.

13. The apparatus according to claim 12,  
further comprising:

a deciphering device

deciphering digital information  
received by said digital information receiver when  
the digital information is ciphered, and providing  
the deciphered digital information to said converter,  
and

deciphering digital information read  
by said drive device when the digital information is  
ciphered, and providing the deciphered digital  
information to said converter.

14. The apparatus according to claim 13,  
further comprising:

a billing manager  
managing billing based on a  
utilization of the digital information received by  
said digital information receiver, and  
managing billing based on a  
utilization of the digital information read by said  
drive device.

15. The apparatus according to claim 12,  
wherein said converter comprises:

an extender  
extending digital information  
received by said digital information receiver when  
said digital information is compressed, and  
extending said digital information  
read by said drive device when said digital  
information is compressed.

SUB 37 16. An apparatus comprising:  
a communication path providing digital data;  
a storage medium storing digital data;  
a converter converting digital data into at  
least one of the group consisting of visible and  
audible data; and  
a switch having  
a first switch position which  
connects digital data provided by the  
communication path to the converter so that the  
converter converts the digital data into at least one  
of the group consisting of visible and audible data,  
a second switch position which  
connects digital data read from the storage medium  
to the converter so that the converter converts the  
digital data read from the storage medium into at  
least one of the group consisting of visible and  
audible data, and  
a third switch position which  
connects digital data provided by the  
communication path to the storage medium so that  
the digital data provided via the communication  
path is stored in the storage medium.

17. The apparatus according to claim 16,  
further comprising:

a deciphering device which,

when the switch is in the first switch position and the digital data provided by the communication path is ciphered, deciphers the digital data before the digital data is provided to the converter, so that the converter receives and converts the deciphered digital data, and,

when the switch is in the second position and the digital data read from the storage medium is ciphered, deciphers the digital data read from the storage medium before the digital data is provided to the converter, so that the converter receives and converts the deciphered digital data.

18. The apparatus according to claim 16, further comprising:

a billing manager managing billing based on a utilization of digital data provided by the communication path, and managing billing based on a utilization of digital data read from the storage medium.

19. The apparatus according to claim 16, wherein the converter comprises:

an extender extending digital data provided by the communication path when the digital data is compressed, and extending digital data read from the storage medium when digital data is compressed.

54B A4 20. An apparatus comprising:  
a communication path providing digital data;  
a storage medium storing digital data;  
a converter converting digital data into at least one of the group consisting of visible and audible data;  
a decoder decoding encrypted digital data;  
and  
a switch having  
a first switch configuration which,  
when non-encrypted digital data is provided by the communication path, connects the digital information provided by the communication path to the converter without passing through the decoder so that the converter converts the digital data into at least one of the group consisting of visible and

audible data.

20 a second switch/configuration which  
when encrypted digital data is provided by the  
communication path, connects the digital  
information provided by the communication path to  
the converter and the decoder so that the encrypted  
digital data is decoded by the decoder and then the  
25 decoded digital data is converted by the converter  
into at least one of the group consisting of visible  
and audible data.

30 a third switch configuration which,  
when non-encrypted digital data is read from the  
storage medium, connects the digital data read from  
the storage medium to the converter without passing  
through the decoder so that the converter converts  
the digital data into at least one of the group  
consisting of visible and audible data.

35 a fourth switch configuration which,  
when encrypted digital data is read from the storage  
medium, connects the digital data read from the  
storage medium to the converter and the decoder so  
that the encrypted digital data is decoded by the  
decoder and then the decoded digital data is  
40 converted by the converter into at least one of the  
group consisting of visible and audible data, and

45 a fifth switch configuration which  
connects the digital data provided by the  
communication path to the storage medium so that  
the digital data provided via the communication  
path is stored in the storage medium.

21. A switch comprising:

5 a first switch position which connects digital  
data provided by a communication path to a  
converter that converts converts the digital data  
into at least one of the group consisting of visible  
and audible data;

10 a second switch position which connects  
digital data read from a storage medium to the  
converter so that the converter converts the digital  
data read from the storage medium into at least one  
of the group consisting of visible and audible data;  
and

a third switch position which connects the  
digital data provided by the communication path to

005060-62645960

15 the storage medium so that the digital data provided  
via the communication path is stored in the storage  
medium.

22. An apparatus comprising:  
a first means which connects digital data  
provided by a communication path to a converter  
that converts converts the digital data into at least  
5 one of the group consisting of visible and audible  
data;

a second means which connects digital data  
read from a storage medium to the converter so that  
the converter converts the digital data read from the  
10 storage medium into at least one of the group  
consisting of visible and audible data; and

a third means which connects the digital data  
provided by the communication path to the storage  
medium so that the digital data provided via the  
15 communication path is stored in the storage  
medium.

005060-62645960